



# MYLANDS

ESTABLISHED LONDON 1884

## PRODUCT DATA SHEETS

### Semi – Permanent Floor Paint

<b>General</b>	<p>Semi-Permanent Floor Paint is a one-coat pigmented water-based paint for non-porous floors. It is quick drying and hard wearing but can be easily removed after use with Mylands Semi-Permanent Floor Wash solution, which is also water based. It has been specifically designed for use in the Film and TV industries, where Semi-Permanent Floor Paint is the Industry standard for temporary and semi-permanent floor, plastic and metal coating.</p>																										
<b>Product Codes</b>	<table border="1"> <thead> <tr> <th>Product</th> <th>Product Size</th> <th>Product Code</th> </tr> </thead> <tbody> <tr> <td>Semi - Permanent Floor Paint Black Dead Matt</td> <td>10L</td> <td>33 700 5320</td> </tr> <tr> <td>Semi - Permanent Floor Paint Black Matt</td> <td>10L</td> <td>33 700 2110</td> </tr> <tr> <td>Semi - Permanent Floor Paint Black Semi Gloss</td> <td>10L</td> <td>33 700 2060</td> </tr> <tr> <td>Semi - Permanent Floor Paint Black Gloss</td> <td>10L</td> <td>33 700 2000</td> </tr> <tr> <td>Semi - Permanent Floor Glaze Gloss</td> <td>5L &amp; 10L</td> <td>33 700 1900</td> </tr> <tr> <td>Semi - Permanent Floor Glaze Matt</td> <td>5L</td> <td>33 700 1905</td> </tr> <tr> <td>Semi - Permanent Floor Wash</td> <td>1L, 5L &amp; 25L</td> <td>33 700 1920</td> </tr> </tbody> </table>	Product	Product Size	Product Code	Semi - Permanent Floor Paint Black Dead Matt	10L	33 700 5320	Semi - Permanent Floor Paint Black Matt	10L	33 700 2110	Semi - Permanent Floor Paint Black Semi Gloss	10L	33 700 2060	Semi - Permanent Floor Paint Black Gloss	10L	33 700 2000	Semi - Permanent Floor Glaze Gloss	5L & 10L	33 700 1900	Semi - Permanent Floor Glaze Matt	5L	33 700 1905	Semi - Permanent Floor Wash	1L, 5L & 25L	33 700 1920		
Product	Product Size	Product Code																									
Semi - Permanent Floor Paint Black Dead Matt	10L	33 700 5320																									
Semi - Permanent Floor Paint Black Matt	10L	33 700 2110																									
Semi - Permanent Floor Paint Black Semi Gloss	10L	33 700 2060																									
Semi - Permanent Floor Paint Black Gloss	10L	33 700 2000																									
Semi - Permanent Floor Glaze Gloss	5L & 10L	33 700 1900																									
Semi - Permanent Floor Glaze Matt	5L	33 700 1905																									
Semi - Permanent Floor Wash	1L, 5L & 25L	33 700 1920																									
<b>Technical Data</b>	<p>Semi-Permanent Floor Paint is a one-coat, pigmented, water-based paint for non-porous floors. It is quick-drying and hardwearing but can be easily removed after use with Mylands Semi-Permanent Floor Wash solution, both paint and remover are water-based.</p> <p>If Studio time is short, the paint can be overcoated with a different colour for the next show (this may result in a small gloss increase due to gloss migration). The resulting multi-coat system can then still be easily removed with Mylands Semi-Permanent Floor Wash (may require more time/multiple applications of solution).</p> <p>Semi-Permanent Floor Paint is not immediately affected by water spillage - it is water soak resistant for 16 to 24 hours.</p> <p>The floor paint is available in three levels of gloss:</p> <table border="0"> <tr> <td>A. Dead Matt</td> <td>up to 5%</td> </tr> <tr> <td>B. Matt</td> <td>5 - 10%</td> </tr> <tr> <td>C. Semi - gloss</td> <td>30 - 40%</td> </tr> <tr> <td>D. Gloss</td> <td>70 - 80%</td> </tr> </table> <p>Semi-Permanent Floor Paint may be overcoated with Semi-Permanent Floor Glaze Gloss or Matt to change the sheen level.</p>			A. Dead Matt	up to 5%	B. Matt	5 - 10%	C. Semi - gloss	30 - 40%	D. Gloss	70 - 80%																
A. Dead Matt	up to 5%																										
B. Matt	5 - 10%																										
C. Semi - gloss	30 - 40%																										
D. Gloss	70 - 80%																										
<b>Application</b>	<p>The paint is supplied ready for use and should not be thinned, except for decorative effect and can be applied by brush or roller.</p>																										

	<p>It is best to apply the paint in as thin a film as possible while still giving sufficient opacity, only building or overcoating with another colour if absolutely necessary.</p> <p>Do not apply to porous surfaces as permanent staining can result from the</p>
<b>Drying Time</b>	Drying time is 1 to 3 hours depending on the thickness of the film applied and the temperature and humidity of the studio. Air conditioning will help speed up the drying time, if blowers are used to speed drying, direct airflow parallel with floor, not down onto the paint surface.
<b>Coverage</b>	Coverage will depend on application method and film weight applied but should be between 10 – 15m <sup>2</sup> per litre.
<b>Thinners</b>	The paint is supplied ready for use and should not be thinned, except for decorative effect. If deemed necessary to thin, use water (sparingly).
<b>Removing</b>	<p>1L of Semi-Permanent Floor Wash is to be mixed with 9L of water to make a 10L solution, which should cover 20 m<sup>2</sup> (single layer of Semi-Permanent Floor Paint).</p> <p>Apply Mylands Semi - Permanent Floor Wash Solution and let it react for 30-45 minutes, then scrub the floor with a cleaning machine or manually. Depending on the size of the studio either vacuum clean or hose off the paint loose particles. The wash off solution will normally destroy a single coat in 5-10mins, multiple coats may take longer or require multiple solution applications.</p> <p>Disposal: In our opinion, the washed off coating (suitably filtered through a coarse sieve to remove large flakes) may be disposed of in main drains. However, please consult with your local authority before doing so.</p>
<b>Colour Matching</b>	<p>Semi - Permanent Floor Paint is available in black from stock but can be matched to any colour on most readily available colour cards, including BBC colour range, Mylands 9000 range, BS colours, RAL colours, etc, and any special colour (colour pattern required). A minimum of 24 hours' notice is required for these matches. Remember to specify sheen level required when ordering.</p> <p>All Semi - Permanent Floor Paint colours may be intermixed to produce different colours and gloss levels, as well as being overcoated with Semi - Permanent Floor Glaze in Matt or Gloss to change the sheen level.</p>
<b>Equipment Cleaning</b>	Wash rollers and brushes after use (before paint dries onto bristles) with water, a little detergent can be added if needed.
<b>Physical Constants</b>	VOC level: 135g/l
<b>Packaging</b>	Semi-Permanent Floor Paint is available in 10 litre containers as standard.
<b>Storage</b>	Protect from frost. Store above 5°C.
<b>Health and Safety</b>	Refer to Mylands Floor Paint MSDS before use

Updated 13/11/2018

For further information visit our website [www.mylands.co.uk](http://www.mylands.co.uk) or contact us: +44 (0)208 670 9161 sales@mylands.co.uk