



Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer

1370331-1379502, 1391015-1399018

Other means of identification:

Tuotenumerot/Product numbers:

1370331, 1370332, 1370518, 1371004, 1371015, 1371018, 1372011, 1373002, 1373020, 1373027, 1375002, 1375009, 1375010, 1375013, 1376005, 1377042, 1377043, 1378014, 1379002, 1379005, 1379011, 1379016, 1379018, 1379502, 1370331-EU, 1370332-EU, 1370518-EU, 1371015-EU, 1371018-EU, 1372011-EU, 1373027-EU, 1374005-EU, 1375009-EU, 1375013-EU, 1376005-EU, 1377042-EU, 1377043-EU, 1378014-EU, 1379005-EU, 1379005M, 1379005M-EU, 1379011-EU, 1379016-EU, 1391015-EU, 1391018-EU, 1392011-EU, 1393002-EU, 1394007-EU, 1395013-EU, 1396005-EU, 1396021-EU, 1397043-EU, 1398014-EU, 1398025-EU, 1399005-EU, 1399016-EU, 1399018-EU

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Maston Oy Teollisuustie 10 FI 02880 Veikkola - Finland Phone: +358 20 7188 580 maston@maston.fi www.maston.fi

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 3: Pressurised container: May burst if heated., H229

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning

Hazard statements:

Aerosol 3: H229 - Pressurised container: May burst if heated.

Precautionary statements:

P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

Supplementary information:

 $\hbox{EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.}$

UFI: 94K0-804J-800E-EU7D

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3,1 Substance:

^{**} Changes with regards to the previous version

^{**} Changes with regards to the previous version





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration		
CAS:	115-10-6	Dimethyl ether(1)	imethyl ether(1) ATP CLP00				
EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37- XXXX		Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	⋄ ◆	22 - <24 %		
CAS:	13463-67-7	Titanium dioxide (ae	rodynamic diameter ≤ 10 μm) ⁽²⁾	ATP ATP14			
EC: 236-675-5 Index: 022-006-00-2 REACH: 01-2119489379-17- XXXX		Regulation 1272/2008	Carc. 2: H351 - Warning	&	1 - <2,5 %		
CAS:	141-43-5	2-aminoethanol(1)		ATP CLP00			
EC: 205-483-3 Index: 603-030-00-8 REACH: 01-2119486455-28- XXXX		Regulation 1272/2008	Acute Tox, 4: H302+H312+H332; Skin Corr, 1B: H314 - Danger	(1) ♦	<0,2 %		
CAS: 111-76-2		2-butoxyethanol(1)		ATP ATP15			
Index:	EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	(!)	0,1 - <0,15 %		

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
2-aminoethanol	
CAS: 141-43-5	% (w/w) >=5: STOT SE 3 - H335
EC: 205-483-3	

^{**} Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

⁽¹⁾ Substance with a Union workplace exposure limit (2) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 4: FIRST AID MEASURES (continued)

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 3/13





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 50 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Oct	Occupational exposure limits		
Dimethyl ether	WEL (8h)	400 ppm	766 mg/m ³	
CAS: 115-10-6	WEL (15 min)	500 ppm	958 mg/m ³	
2,2´-oxybisethanol	WEL (8h)	23 ppm	101 mg/m ³	
CAS: 111-46-6	WEL (15 min)			
2-butoxyethanol	WEL (8h)	25 ppm	123 mg/m ³	
CAS: 111-76-2	WEL (15 min)	50 ppm	246 mg/m ³	
2-aminoethanol	WEL (8h)	1 ppm	2,5 mg/m ³	
CAS: 141-43-5 EC: 205-483-3	WEL (15 min)	3 ppm	7,6 mg/m ³	
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	WEL (8h)		4 mg/m ³	
CAS: 13463-67-7 EC: 236-675-5	WEL (15 min)			

NULL:

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVS) - EH40/2005

Identification	NULL	NULL	NULL
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	280 mg/g (NULL)	Butoxyacetic acid in urine	Post shift

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	1894 mg/m³	Non-applicable
2-aminoethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-43-5	Dermal	Non-applicable	Non-applicable	3 mg/kg	Non-applicable
EC: 205-483-3	Inhalation	Non-applicable	Non-applicable	1 mg/m³	0,51 mg/m ³
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m³	Non-applicable





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	471 mg/m³	Non-applicable
2-aminoethanol	Oral	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
CAS: 141-43-5	Dermal	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
EC: 205-483-3	Inhalation	Non-applicable	Non-applicable	0,18 mg/m ³	0,28 mg/m ³
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m³	147 mg/m ³	59 mg/m ³	Non-applicable

PNEC:

Identification				
Dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
2-aminoethanol	STP	100 mg/L	Fresh water	0,07 mg/L
CAS: 141-43-5	Soil	1,29 mg/kg	Marine water	0,007 mg/L
EC: 205-483-3	Intermittent	0,028 mg/L	Sediment (Fresh water)	0,357 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,036 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Compulsory use of face mask	Filter mask for particles	CAT III	EN 149:2001+A1:2009	Replace when an increase in resistence to breathing is observed.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0,4 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
^ +	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	**	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 24,31 % weight

V.O.C. density at 20 °C: 215,91 kg/m³ (215,91 g/L)

Average carbon number: 3,78
Average molecular weight: 86,71 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Aerosol
Appearance: Dispersion

Colour: According to the markings on the package

Odour: Not available
Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: -25 - 388 °C (Propellant)

Vapour pressure at 20 °C: 349971 Pa

Vapour pressure at 50 °C: 719940,89 Pa (719,94 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

stNot relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 6/13





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Density at 20 °C: 888 kg/m³ Relative density at 20 °C: 0,888

Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Non-applicable * Recipient pressure:

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable *

Non-applicable *

Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9,2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *
Oxidising properties: Non-applicable *
Corrosive to metals: Non-applicable *
Heat of combustion: Non-applicable *
Aerosols-total percentage (by mass) of flammable Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

*Non-applicable *

*Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 10: STABILITY AND REACTIVITY (continued)

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids Water		Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11,1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: 2-butoxyethanol (3); Titanium dioxide (aerodynamic diameter \leq 10 μ m) (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects, For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 8/13

^{**} Changes with regards to the previous version





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10~\mu m$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10~\mu m$

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether	LD50 oral	>2000 mg/kg	
CAS: 115-10-6	LD50 dermal	>2000 mg/kg	
EC: 204-065-8	LC50 inhalation	308,5 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 dermal	10000 mg/kg	Rabbit
EC: 236-675-5	LC50 inhalation	>5 mg/L	
2-aminoethanol	LD50 oral	1089 mg/kg	Rat
CAS: 141-43-5	LD50 dermal	1100 mg/kg	
EC: 205-483-3	LC50 inhalation	>20 mg/L	
2-butoxyethanol	LD50 oral	1200 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	3000 mg/kg	Rabbit
EC: 203-905-0	LC50 inhalation	>20 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
2-aminoethanol	LC50 349 mg/L (96 h)		Cyprinus carpio	Fish
CAS: 141-43-5		65 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-483-3		22 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
2-aminoethanol NOEC 1,24		1,24 mg/L	Oryzias latipes	Fish
CAS: 141-43-5 EC: 205-483-3		0,85 mg/L	Daphnia magna	Crustacean
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 9/13

^{**} Changes with regards to the previous version





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

Identification	Degradability		Biodegradability	
2-aminoethanol	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 141-43-5	COD	Non-applicable	Period	21 days
EC: 205-483-3	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
2-aminoethanol	BCF	3	
CAS: 141-43-5	Pow Log	-1,31	
EC: 205-483-3	Potential	Low	
2-butoxyethanol	BCF	3	
CAS: 111-76-2	Pow Log	0,83	
EC: 203-905-0	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether	Koc	Non-applicable	Henry	Non-applicable
CAS: 115-10-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-065-8	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable
2-aminoethanol	Koc	0,27	Henry	3,7E-5 Pa·m³/mol
CAS: 141-43-5	Conclusion	Very High	Dry soil	No
EC: 205-483-3	Surface tension	5,025E-2 N/m (25 °C)	Moist soil	No
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
16 05 09 discarded chemicals other than those mentioned in 16 05 06, 16 05 07 or 16 05 08		Non dangerous	

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 10/13





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number or ID number: UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2

Labels: 2.1

14.4 Packing group: N/A

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 190, 327, 344, 625

Tunnel restriction code: D

Physico-Chemical properties: see section 9

Limited quantities: 1 l

14.7 Maritime transport in bulk according to IMO instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.1 UN number or ID number: UN1950
 14.2 UN proper shipping name: AEROSOLS
 14.3 Transport hazard class(es): 2
 Labels: 2

Labels: 2.1 **14.4 Packing group:** N/A **14.5 Marine pollutant:** No

14.6 Special precautions for user

instruments:

Special regulations: 63, 959, 190, 277, 327, 344

EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9
Limited quantities: 1 L

Segregation group: Non-applicable

14.7 Maritime transport in bulk according to IMO

Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number or ID number: UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2

Labels: 2.1 **14.4 Packing group:** N/A **14.5 Environmental hazards:** No

14.6 Special precautions for user

instruments:

Physico-Chemical properties: see section 9 **14.7 Maritime transport in bulk** Non-applicable according to IMO

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 11/13





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 3-iodo-2-propynyl Butylcarbamate, bronopol (INN), , , 2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains Octamethylcydotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988 **15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11):

New declared substances

Titanium dioxide (aerodynamic diameter \leq 10 µm) (13463-67-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

Supplementary information

Texts of the legislative phrases mentioned in section 2:

H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Gas 1A: H220 - Extremely flammable gas.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

- CONTINUED ON NEXT PAGE -

Date of compilation: 19.2.2016 Revised: 12.10.2022 Version: 8 (Replaced 7) Page 12/13





Maston - ZERO eco, water-based spray paint - primer, top coat, lacquer 1370331-1379502, 1391015-1399018

SECTION 16: OTHER INFORMATION (continued)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.