







ZERO[®] SPRAYPAINT



MASTON ZERO® IS THE SAFEST AND ENVIRONMENT FRIENDLIEST SPRAY PAINT EVER MADE!

Because of its unique water-based technology, Maston Zero® does not contain any added solvents making it safe to be used inside and outside with no unpleasant smells. The VOC content is reduced to only 216 g/l making the product completely non flammable and safe to use in any environment. One cross layer is enough to create immediate coverage with a film thickness of 25 to 30 microns and no run downs. The paint can be re-coated any time, wet-on-wet or wet-on-dry. Surface is touch dry after 90 minutes and dry after 48 hours. Maston Zero® is great to use on many projects inside and outside of the house including Polystyrene. The unique formulation contains no solvents in the paint and reduces the contents propellants only to 24% of the weight, allowing more paint inside. NB! Clean the drip nozzle whenever you release the nozzle.

Instructions Do not spray more than 30 seconds without shaking in between. Wipe the nozzle after or before each spray to avoid paint spitting. It is recommended to rinse the nozzle with warm water after use. Make sure the nozzle is dry before next use.





CLEAN UP











BINDER:

Alkyd, Water based

DEGREE OF GLOSS (DIN 67530 60°):

matt 0-25 gloss units satin 40-60 gloss units glossy 80-100 gloss units

HEAT RESISTANCE: 80 °C STORAGE STABILITY: 36 months

RECOAT: always, 5 minutes in between layers

SIZE: 150ml, 400ml

ALKYD

+20°C







Information valid at 20°C, relative air humidity 20% - 70%

