Universal Roof Terminal & Adaptor



KEY FEATURES

- A choice of three colours: Anthracite, Sepia & Terracotta.
- Comes with a stepped adaptor for Ø100/110/125/150/160mm duct connections.
- Waterproof/ weatherproof membrane used at junctions/ changes in fabric.
- Quick and easy to install saves time and money.
- No toxic risk environmentally friendly and recyclable.
- 80% lighter than lead less risk of injury.
- BRE wind tunnel tested, BBA Certified, and approved by NHBC.

Universal Roof Terminal & Adaptor

260 x 550 x 230 mm roof terminals are suitable for use on all tile and slate pitched roofs without the need to identify the make or design of the tiles or slates or the pitch of the roof.

Each terminal comprises of a hood on a circular upstand (Ø160 mm) with a 500 mm x 500 mm non-lead, weatherproof membrane and adaptor which

can be cut to size, allowing connections to Ø100 mm, 110 mm, 125 mm, 150 mm & 160 mm diameter ducting.

Offered in three distinct colours - Anthracite, Sepia & Terracotta to suit most roof applications.

















1

airflow.com

MODELS


Colours	Sizes available				
Anthracite	ø100 mm / 110 / 125 / 150 / 160 mm				
Terracotta	ø100 mm / 110 / 125 / 150 / 160 mm				
Sepia	ø100 mm / 110 / 125 / 150 / 160 mm				




TECHNICAL DATA

Duct size	Vent free area	Pressure / Airflow Resistanc Readings (Pa) (vent system pressure)					
(mm)	(mm²)	100 mm³/h	200 mm³/h	400 mm³/h	800 mm³/h		
100	7,850	3.0	12.0	48.0	192.0		
110	8,850	4.5	18.0	72.0	288.0		
125	12,250	5.3	21.2	84.8	339.2		
150	17,775	6.5	26	104	416		
160	18,750	6.5	26	104	416		
Part No. Anthracite	90000349						
Part No. Terracotta	90000351						
Part No. Sepia	90000350						

DIMENSIONS (mm)







Call: 01494 525252

Visit: airflow.com

Certificate No. FMS. SPRIGS.