


CIBSE TM65 Embodied Carbon 'Mid-level' Calculation

Assesment Date:	26.04.2024	Embodied Carbon Result with 'TM65 Calculation' Method Total:
Organisation:	Airflow Developments Ltd	
Contact email:	info@airflow.com	3242 kg CO₂e




DUPLEXbase PT 2800 - Product Information

Type of product	Mechanical Ventilation with Heat Recovery (MVHR)	
Maximum power input (kW)	1.66	
Product weight (kg)	518	
Material breakdown for at least 95% of the product weight? (Y/N)	Y	
Service life of the product (years)	15	
Energy consumption of the factory per kg of product (kWh)	0.43	
Location of manufacture	Europe	
Product Complexity	Category 3: High	

TM65 Calculation Methodology

TM65 calculation methodology outlines the need for product embodied carbon assessment related to building services engineering systems. Embodied carbon is understood as the greenhouse gas emissions associated with the manufacture of a product, its installation, maintenance, repair, replacement, and end of life. It covers the whole life cycle, excluding operational aspects and the potential recovery, reuse or recycling of materials. [Ref. CIBSE TM65 Embodied carbon in building services: A calculation methodology (2021)]



CIBSE TM65 Embodied Carbon 'Mid-level' Calculation


Embodied Carbon Results Breakdown (kg CO₂e)

A1: Material extraction	1834.00
A2: Transport	96.00
A3: Manufacturing	245.00
A4: Transport to Site	20.00
B3: Repair	226.00
C2: Transport	6.00
C3: Waste Processing	61.00
C4: Disposal	2.70

Total embodied carbon results (kg CO₂e) Mid-Level:

3242

Embodied Carbon Results Breakdown (kg CO₂e)



Assumptions

A1: Material carbon coefficient source	TM65 Table 2.1
A2, A4 and C2	TM65 Table 4.7 & Table 4.8
A2 and A3 Product complexity	TM65 Table 4.9
A3: Manufacturing	TM65 Table 4.10 & Table 4.11
A4: Transport to site	TM65 Table 4.12
C3 and C4	TM65 Table 4.14 & Table 4.15
B3: Repair	10% (TM65 Assumption)

80001614 - Issue 1 05/24



Call: 01494 525252

Visit: airflow.com