

Aura Smart



Key Features

- Two speed axial fan
- Flow rate up to 133 m³/hr
- Interchangeable spigots - 100/125mm
- Modern compact styling - optional front covers to match décor
- Quick and easy to fit
- A separate remote controller
- Versatile positioning - portrait or landscape
- Exceptionally quiet - 21 dB(A)
- Energy efficient low watt motor - 3.8W
- Advanced controls for ultimate user comfort
- Universal voltage 100/240v - 50/60Hz
- IP44 rating
- Complies with Building Regulations
- 5 year warranty

Aura Smart

The Aura Smart is an innovative low energy axial fan with a unique design for ease of installation and maintenance. The fan is extra slim and with optional colour covers available, it will blend perfectly into the décor of any room. The fan is suitable for mounting anywhere outside of Zone 2 of your wetroom.

The fan comes with interchangeable spigots giving the user the option to use 100mm or 125mm ducting and increase the flow rate accordingly.

This smart fan is available with either humidity timer control or motion sensor humidity timer control giving the user the benefit of achieving the perfect micro climate within their home. Aura Smart has a one-touch control panel beneath the cover for control of the fan. A separate remote controller is also included for convenient control of all the functions – it's a Smart Fan!

Interval ventilation occurs automatically every 15 hours for a period of 2 hours - this ensures regular movement of the air and keeps the room fresh.



Models

Humidity Timer Humidity sensor activates fan - if humidity rises by less than 20% within 10 minutes, run on time reverts to 15 minutes instead of the preset rates of 30, 45 or 60 minutes.

Motion Sensor Humidity Timer PIR sensor activates fan to switch on - overrun timer kicks in - can be set at 5, 15 or 30 minutes. If humidity sensor activates the fan – run on time, to clear humidity can be set at 30, 45 or 60 minutes. If the humidity rises by less than 20% in 10 minutes the overrun time will revert to 15 minutes.



Technical Data


Specification	Aura Smart HT		Aura Smart MSHT	
Spigot size	100mm	125mm	100mm	125mm
Air flow m ³ /hr*	72 / 106	83 / 133	72 / 106	83 / 133
Air flow l/sec*	20 / 29	23 / 37	20 / 29	23 / 37
Fan type	Axial		Axial	
Controls	Humidity Timer		Motion Sensor Humidity Timer	
Mounting	Wall		Wall	
Sound pressure dB(A)@3m	22 / 31	21 / 32	22 / 31	21 / 32
Adjustable delay start (min)	0, 2, 5		0, 2, 5	
Adjustable timer (min)	5, 15, 30		5, 15, 30	
Adjustable timer on humidity activation (min)	30, 45, 60		30, 45, 60	
Interval timer, auto start (hrs)	15		15	
Power watts	Up to 3.8		Up to 3.8	
Specific Fan Power (SFP)	0.13	0.1	0.13	0.1
Building Regulations ADF	Yes		Yes	
Voltage	100-240V/50-60Hz		100-240V/50-60Hz	
Rating	IP44		IP44	
Weight (Kg)	0.63		0.63	
Dimensions (H x W x D)mm	206x152x86		206x152x86	
Part No.	90000384		90000385	

Covers		
HT	Colour	MSHT
90000386	Marble	90000416
90000387	Silver	90000417
90000388	Champagne	90000418
90000389	Red	90000419
90000390	Mauve	90000420
90000391	Graphite	90000421
90000392	Black	90000422




* Air flow at free discharge

Dimensions (mm)



Model	A	B	C	D	E
Aura Smart	206	100/125	152	57	29

Performance



Controls and Accessories

A range of accessories including flexible and rigid ducting kits, controls, switches and grilles are available.

Call: 01494 560800 **Visit: airflow.com**



Airflow Developments Limited
Aidelle House, Lancaster Road,
Cressex Business Park,
High Wycombe, Buckinghamshire,
United Kingdom, HP12 3QP

E-mail: info@airflow.com
Telephone: +44 (0) 1494 525252
airflow.com

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request

