Aventa In-Line

Bathroom, en-suite, utility room and kitchen ventilation



KEY FEATURES

- In-Line mixed flow fan
- Flow rate up to 144 l/s (520 m³/h)
- Designed for ducted installations
- High pressure, low noise
- Compact and quiet in operation
- Two speed (normal and boost)
- Adjustable Run on Timer version available
- Access to motor and impeller without dismantling ductwork
- Suitable for variable speed control
- Low Watt motor 30 W
- IPX4 rating

1

- Complies with Building Regulations
- 3 year warranty

Aventa In-Line range

TIMER

BASIC

SWITCHING

The Aventa range of in-line fans provides a quiet, powerful and compact remote duct mounted ventilation solution. Units are available in high performance two speed versions. Less bulky than larger in-line centrifugal fans means flexibility of installation. Remote loft space or service shaft location etc is easily achieved.

With high flow/high pressure development characteristics they can be used with flexible ducting and flat duct systems to ensure compliance with Building Regulations guidance ensuring installed performance and extraction conditions are met.

Combining two Aventa fans allows for even more powerful operation. Mounting in parallel (left hand image on facing page) doubles the air flow, whilst two fans in series (right hand image on facing page) leads to a doubling of the air pressure for longer duct runs.







MODELS


Basic	Basic remote switching
Timer	Adjustable timer overrun between 2 and 30 minutes




TECHNICAL DATA

Specification	Aventa 150B	Aventa 150T		
Air flow m ³ /h	405 / 520			
Air flow I/s	112 / 144			
Fan type	Mixed Flow			
Controls	Basic	Timer		
Mounting	In-Line			
Sound Pressure dB(A)@3 m	33 / 44			
Power Watts	30 / 60			
Amps	0.17 / 0.27			
Building Regulations ADF	Yes			
Duct diameter (mm)	150			
Voltage	230 V / 1 ph / 50 Hz			
Rating	IPX4			
Material finish	ABS			
Weight (kg)	2.65			
Dimensions (H x W x D) mm	250 x 295 x 185			
Part No.	9041089	9041090		
Speed controller No.	9041565	9041565		

DIMENSIONS (mm)





Model	Α	В	С	D	E
AV150	146	295	250	146	223


Double the flow - mount in parallel

Double the pressure - mount in series





PERFORMANCE



CONTROLS AND ACCESSORIES

A range of accessories including flexible and rigid ducting kits, controls, switches and grilles are available.

Call: 01494 525252



Airflow Developments Limited Aidelle House, Lancaster Road, Cressex Business Park, High Wycombe, Buckinghamshire, United Kingdom, HP12 3QP E-mail: info@airflow.com Telephone: +44 (0) 1494 525252

airflow.com

Visit: airflow.com

80001027 - Issue 2 11/20

