

RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636



Product features

- Energy saving replacement for halogen ES111 GU10 lamps • High lumen output - 1000lm • Compact design, same diameter as the halogen lamp • Stippled lens to help reduce glare and recreate the halogen light effect • 25° beam angle • High lumen intensity - 4500 cd • 90% energy saving - A+ EEL rating • 11.5 W equivalent to 122W • Dimmable • 25,000 H average rated life, last 12.5 times longer than halogen alternatives • 0.90 power factor • > 50,000X switching cycle • High lumen efficacy -87 lm/W • CRI 80



NOTES

undefined

PRODUCT OVERVIEW

Product name	RefLED ES111 1000LM DIM 830 25°SL
Technology	LED
Watt (Rated) (W)	11.5
Lamp shape	Reflector
Type	RefLED ES111
Cap/Base	GU10
Fixture rating	Open
General application	Hospitality, Retail, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4740563
E-number SE	8292815
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	25
Wattage (W)	11.5
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288276366

DATA TABLE

General data

Product name	RefLED ES111 1000LM DIM 830 25°SL
Technology	LED

RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636

Watt (Rated) (W)	11.5
Lamp shape	Reflector
Type	RefLED ES111
Cap/Base	GU10
Fixture rating	Open
General application	Hospitality, Retail, Residential & Consumer, Museums & Galleries
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740563
E-number SE	8292815
Warranty	3 years

Optical data

Rated Luminous Flux Useful (lm)	1000
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Rated Luminous Intensity (cd)	4500
Beam Angle (°)	25

Electrical data

Wattage (W)	11.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	2
Current (A)	55
Mains voltage (V)	220-240V~
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	>50000
Transformer required	Yes
Dimmable	Yes
Lamp Energy Label (class)	F
kWh per 1000 hours burning time	12
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	65
Nominal Product Diameter (mm)	111
Weight (kg)	0.155

RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636

Packaging

Single packaging type	Carton
Product EAN number	5410288276366
Packaging single length / height (cm)	11.5
Packaging single width (cm)	11.5
Packaging single depth (cm)	7.8
DUN14 (inner)	25410288276360
Units per inner package	6
Packaging inner length / height (cm)	36.5
Packaging inner width (cm)	12.5
Packaging inner depth (cm)	17.0
DUN14 (outer)	15410288276363
Units per outer package	24
Packaging outer length / height (cm)	38.3
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	36.5

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures