



By Appointment to Her Majesty Queen Elizabeth II
 Manufacturers of French Polishes, Stains and Wax Polishes
 John Myland Limited, London

MYLANDS

ESTABLISHED LONDON 1884

PRODUCT DATA SHEETS CRACKLE GLAZE

General	Designed to give an antique, cracked and worn appearance to newly painted surfaces.	
Product Codes	Product Crackle Glaze	Product Code 13 799 8088
Technical Data	Used in the restoration and reproduction furniture trade, in special effects and more recently the upcycling of furniture, it is an easy, low odour method to create an aged look.	
Application	<p>First choose two complimenting or contrasting colours of water based emulsion, one as a base coat (the colour of the cracks) and one as a topcoat.</p> <p>Apply the emulsion as normal with a good quality brush, shake the crackle glaze well and apply over the base emulsion. Once dry, apply the top coat of emulsion, being careful to brush in one direction only in singular strokes, over brushing will cause it to mix with the emulsion underneath and not work.</p> <p>It may help to thin the top coat with a little water to make it easier to apply, it is also worth noting that the thicker the top coat, the bigger the cracks can be. It should begin cracking soon after you have applied it.</p>	
Drying Time	Drying time is dependent on temperature and humidity but should be around 1 hour-90mins.	
Coverage	This will be dependent on substrate & effect required but approximately 10-14m ² per Litre	
Thinners	Water.	
Equipment Cleaning	Water.	
Maintenance	If you choose to, the object can be carefully sealed after with a varnish or lacquer, keep the object away from extreme fluctuations in temperature.	
Packaging	Mylands crackle glaze is available in the following containers: 1Litre & 5Litre	
Physical Constants	VOC Level: 12g/l	
Storage	Store in frost-free conditions above 5°C.	
Health and Safety	Refer to Mylands MSDS before use.	