

PRODUCT INTRODUCTION (GS1408)

GLOSS SEALER

INTRODUCTION

Jesmonite® Gloss Sealer is a pure acrylic coating compatible with all Jesmonite composites, from AC100 to AC830. It's a durable, flexible product designed with the inclusion of a specially formulated Gloss finish, exactly what many users have been asking for. This new product is easily applied by way of brush, roller, or spray and similarly can be diluted in a variety of formats to achieve variations in finish.

We firmly believe that the introduction of Gloss Sealer will be welcomed in the arts, crafts and creative sectors whilst being high performing enough for commercial and scaled works.

Products treated with Gloss Sealer will require re-coating at 6-to-10-year intervals unless they are being cleaned regularly, then re-coating is recommended sooner. Overcoating with this product is suitable. Ensure that the surface is dust and contaminant free prior to re-application.

GLOSS SEALER APPLICATION

We recommend for best results that two coats of Gloss Sealer should be applied, with the first coat being diluted with 10 to 50% water. Diluting the first coat will aid the bonding process of the Gloss Sealer. The second coat is applied once the initial diluted coat is touch dry. Do not allow the first coat to dry completely before applying the second coat. The application of several thin coats is preferable to one thick coat.

Remember that small quantities of Gloss Sealer go a long way - do not over apply the product and ensure you work with small doses to control the process.



For further information on this, and other products and to see how Gloss Sealer is applied please visit our YouTube:

<https://www.youtube.com/@jesmonite>

KEY BENEFITS

- Increased Water & Stain Resistance
- Easily Applied, Various Methods
- High Gloss Finish
- Cross Product Compatibility

Jesmonite® is a Registered Trademark

The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended.

Contact Details
Jesmonite Limited
Challenge Court

Bishops Castle
Shropshire SY9 5DW
United Kingdom

Tel. +44 (0)1588 630302
Fax. +44 (0)1588 630304
www.jesmonite.co.uk