

TECHNICAL DATA SHEET (TDS/JDP/23)

*Decorative Paints***JESMONITE**
MADE FROM**JESMONITE**
MADE FROM

PRODUCT DESCRIPTION

Jesmonite® Decorative Paints are Sol-silicate based paint systems for use on all Jesmonite® surfaces to provide a colourwash, solid or semi-transparent finish. Offering water resistance, vapour permeability and forming a chemical crystalline bond with the substrate.

FIELD OF APPLICATION

Jesmonite® Decorative Paints can be applied neat or with the Jesmonite® Dilution & Priming Agent to create varied finishes including adjustment of translucency for both interior and exterior use.

APPLICATION INSTRUCTIONS

Please refer to Jesmonite® Decorative Paints User Guide (UG/JP/22).

SPECIFICATIONS

Mix ratio	Varied (Refer to User Guide)
Specific Weight	1.2 – 1.3 g/cm ³
Vapour Diffusion Resistance	sd < 0.01m

STORAGE

Approximately 12 months, if kept cool but frost free in tightly closed containers.

DISPOSAL

EC Waste Code No. 08 01 12*

**Any material residue MUST be emptied out of containers prior to recycling.*

SAFETY INSTRUCTIONS

Cover surfaces which are not to be treated with the product.

Suitably protect eyes and skin from splashes of product. Keep out of reach of children.

Please, refer to the Material Safety Data Sheet.

Jesmonite® is a Registered Trademark

The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended.

Contact details

Jesmonite Limited
Challenge Court
Bishops Castle
Shropshire
SY9 5DW
United Kingdom

Tel: +44 (0)1588 630302
Fax: +44 (0)1588 630304
www.jesmonite.com