



technical data sheet

ACRYLIC COLOURANT

PRODUCT DESCRIPTION

Super high quality acrylic pigment specifically formulated to give superior colour saturation. Concentrated colourant can be used with all water-based products from scumble, stain, emulsion paint, varnish and interior paint, to glue, filler, masonry paint, tile grout and cement.

Concentrated colourant can be used with all water-based coatings used in the theatre, film, scenery decorative paint industry.

Pigment dispersed in a mixture of surfactant, humectant, preservative and water. It does not contain Nonyl Phenol Ethoxylates as ingredients or contaminants. We recommend that this product is mixed thoroughly before use.

The pigment content is approximately 50%, the particle size is 5m.

Concentrated non-ionic and anionic dispersion of pigment.

The product has high colour strength and good compatibility with most aqueous coatings.

All colourants are intermixable to give any colour or shade.

available in: yellow, blue, green, red, crimson, yellow oxide, red oxide, prussian blue, ultramarine, magenta, raw umber, burnt umber, burnt sienna, mahogany dark oak, black, white, raw sienna, antique pine, medium oak,

MIXING

Acrylic Colorants may be added up to a maximum of 10 % by weight. But considering that it is highly concentrated, you can obtain best results by adding a minimum. The maximum additions are: 10 %

Ensure product is well mixed, do not mix batch numbers.

Pour into a suitable container and mix with another colour if required.

CAUTION

Concentrated colourant requires very small additions to vary the colour.

Test colour and mix before applying.

COVERAGE

dependant on base medium.

CLEAN UP

Any equipment used can be cleaned using soap and water. Wipe any excess off surfaces with a damp cloth.

PACKAGING

50g/US1.78oz

STORAGE

Store in unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to access the suitability of the product on a test area before application.

Date of Issue: August 2013

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk