



Technical Data Sheet



Sellotape

Zero Plastic Tape

Technical Data Sheet
Ref: SE7500
Issued: 13.10.22
Number of pages: 3

CHARACTERISTICS

- Clear stationery tape consisting of cellulose film coated with natural rubber based pressure sensitive adhesive
- Produced from plant based renewable resources
- Zero plastic content
- Recycled and recyclable cardboard core and packaging
- Easy to tear by hand – no need to use scissors or teeth
- Excellent instant adhesion to paper, card etc.
- Anti-tangle
- Meets requirements for industrial compostability (EN13432:2000)

APPLICATION FIELD

General purpose stationery tape for household and office use

INSTRUCTIONS FOR USE

1. Ensure all surfaces to be bonded are clean, dry and free from dust
2. Unroll desired length of tape from roll
3. Tear tape by holding tape between thumb and forefingers and applying sharp tearing action across the width of the tape:





1. Apply to surfaces taking care not to twist or crease the tape:



2. Apply light finger pressure onto the applied tape in order to ensure good adhesion:



TECHNICAL DATA

Composition	Cellulose film coated with natural rubber based pressure sensitive adhesive	
Appearance	On roll:	Light golden roll of tape
	Unwound:	Clear tape
Roll dimensions	Width 24mm x length 30m	
Bonding speed	Immediate when applied to substrate with light finger pressure	
Total thickness	45µm	
Peel adhesion (stainless steel)	≥3N/cm	
Tensile strength	≥15N/cm	
Elongation at break	≥13%	
Shelf Life at 20 °C	At least 18 months	

LIMITATIONS

Do not use on dusty, dirty, unstable, fibrous, damp or wet surfaces

Not suitable for sealing heavy weight cartons



STORAGE

Store in a cool, dry place

HEALTH AND SAFETY

This product is safe to use for the intended application

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

e.mail: technical.services@henkel.co.uk