

Model. FWCS45SK

45Amp DP Cooker + Socket

Features & Benefits

- BS 3676 AC ONLY, SUPPLIED WITH M3.5X30MM FIXING SCREWS
- CABLE CLAMP ACCOMODATES 4MM ? TO 16MM? CABLE FOR 45AMP
- TERMINAL CAPACITY 3X2.5MM? FOR 20/25AMP

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 13mm
Front Plate Depth (mm)	13mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	10mm ²
Rated Load Capacity (Amps)	45A
Frequency (Hz)	50/60Hz
Number Poles	Double Pole
Approvals	BS3676-BSEN60669
Kite Mark / ASTA	KM73110
Performance Data	
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	

