





45Amp DP Switch Tall Twin Plate + Neon

## Features & Benefits

- BS3676 AC only
- Supplied With M3.5x30mm Fixing Screws
- Cable Clamp accommodates 4mm² to 16mm² Cable for 45Amp
- Terminal Capacity 3x2.5mm² for 20/25Amp

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
  Do not dispose of decommissioned fitting in household waste
  Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 13mm
Front Plate Depth (mm)	13mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm²)	10mm²
Rated Load Capacity (Amps)	45A
Frequency (Hz)	50/60Hz
Number Poles	Double Pole
Approvals	BS3676-BSEN60669
Kite Mark / ASTA	KM73110
Performance Data	
Switch (1 / 2) etc	1 Switch
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	

