

Model. FWS12

10Amp 1 Gang 2 Way Switch



Features & Benefits

- FLEX OUTLETS AT LOWER EDGE BY KNOCKOUT
- SUPPLIED WITH M3.5 X30MM FIXING SCREWS
- CABLE CLAMP ACCOMMODATES 2.5MM ? FLEXIBLE CABLE
- FITTED WITH 13AMP FUSE UNLESS SPECIFIED OTHERWISE
- TERMINAL CAPACITY 3X2.5MM ?, 4X2.5MM?(EARTH)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|--------------------------------------|--------------------|
| Colour/Finish | White |
| Dimensions (mm) | 86 x 86 x 9mm |
| Front Plate Depth (mm) | 9mm |
| Fixing Centre (mm) | 60.3mm |
| Minimum Box Depth (mm) | 25mm |
| Electrical | |
| Rated Operating Voltage (v) | 240v |
| Terminal Capacity (mm ²) | 1.5mm ² |
| Rated Load Capacity (Amps) | 10A |
| Frequency (Hz) | 50/60Hz |
| Approvals | BS1363 pt2 |
| Kite Mark / ASTA | KM73110 |
| Performance Data | |
| Switch (1 / 2) etc | 1 Switch |
| Control (1 / 2 Way) | 1 Way |
| Construction | |
| Body | Urea Formaldehyde |
| Warranty (Years) | 25 |
| Other | |