

## Model. FWS32

10Amp 3 Gang 2 Way Switch



### Features & Benefits

- FLEX OUTLETS AT LOWER EDGE BY KNOCKOUT
- SUPPLIED WITH M3.5 X30MM FIXING SCREWS
- CABLE CLAMP ACCOMMODATES 2.5MM ? FLEXIBLE CABLE
- FITTED WITH 13AMP FUSE UNLESS SPECIFIED OTHERWISE
- TERMINAL CAPACITY 3X2.5MM ?, 4X2.5MM? (EARTH)

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm <sup>2</sup> )	1.5mm <sup>2</sup>
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Approvals	BS1363 pt2
Kite Mark / ASTA	KM73110
Performance Data	
Switch (1 / 2) etc	3 Switches
Control (1 / 2 Way)	2 Way
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	