

Model. FWSSK2

13Amp Twin Switch Socket

Features & Benefits

- Flex outlets at lower edge by knockout
- Supplied with M3.5 x30mm fixing screws
- Cable clamp accommodates 2.5mm² flexible cable
- Fitted with 13A fuse unless specified otherwise
- Terminal capacity 3x2.5mm², 4x2.5mm² (earth)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	2.5mm ²
Rated Load Capacity (Amps)	13A
Approvals	BS1363 pt2
Kite Mark / ASTA	KM73110
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Gang
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	

