

Model. FWSTVFM

Satellite /TV/FM Outlet



Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	2.5mm ²
Frequency (Hz)	50/60Hz
Approvals	BS-800 BS-55518
Performance Data	
Construction	
Body	Urea-formaldehyde
Warranty (Years)	25
Other	

Applications

ISOLATED UNIT-FOR USE IN MULTI - OUTLET COMMERCIAL SYSTEM PROVIDING SAFETY ISOLATION, TV-FM OUTLET-FOR DIRECT CONNECTION TO SINGLE SATELLITE, TV OR FM COAXIAL DOWN LEADS, SUITABLE FOR VHF/UHF TV & VHF RADIO BOTH OUTLETS ACCEPT STANDARD COAXIAL PLUGS TO BS3041, SUPPLIED WITH M3.5X30MM FIXING SCREWS