

No Image

Model. FWTELFM1

Telephone Flush Master

Features & Benefits

- All sockets have IDC type connector
- Flush Mounting Sockets are smaller than Surface Mounting Sockets
- Supplied with M3.5 x 30mm Fixing Screw
- Terminal Capacity 2 x 0.68mm² to BT Specification

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information

| | |
|------------------------|---------------|
| Colour/Finish | White |
| Dimensions (mm) | 86 x 86 x 9mm |
| Front Plate Depth (mm) | 9mm |
| Fixing Centre (mm) | 60.3mm |
| Minimum Box Depth (mm) | 25mm |

Electrical

| | |
|--------------------------------------|---------------------|
| Rated Operating Voltage (v) | 240v |
| Terminal Capacity (mm ²) | 0.68mm ² |
| Frequency (Hz) | 50/60Hz |
| Approvals | BS-800 BS-55518 |

Performance Data

| | |
|---------------------|--------|
| Outlets (1 / 2) etc | 1 Gang |
|---------------------|--------|

Construction

| | |
|------------------|-------------------|
| Body | Urea-formaldehyde |
| Warranty (Years) | 25 |

Other