



## Model. HBLEDNL

60W LED High Bay (Empty Body)

### Features & Benefits

- Fitting only (no control gear or cable), gear box with E40 lampholder - Lamps sold separately
- Suitable for low bay and high bay and uses 60W, 80W, 100W & 120W Corn Lamps
- Fitting supplied with a 19°/50° Aluminium reflector as standard, an optional spare 110° reflector is also available

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	195x240x160mm
Ingress Protection	IP20
Electrical	
Input Voltage (V)	85-265v
Frequency (Hz)	50/60Hz
Wattage (W)	60W upto 120W
Wattage Equivalent (W)	150W, 250W, 400W
Dimmable (Y/N)	N
Approvals	CE
Class	I
Performance Data	
Useful Lumen Output	6300Lm up to 13000Lm
Power Factor	>90
Average Lifespan (Hours)	35,000Hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	50°
LED Type	CL60, CL80, CL100, CL120
Energy Rating (ErP)	A
Sensor	
Emergency	
Construction	
Body Material	Aluminium
Warranty Period (Years)	1Yrs
Other	
Applications	Warehouse and Industrial applications

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**