



## Model. HD2000A

2000W ABS Eco Hand Dryer

### Features & Benefits

- Warm air 2000W ABS Eco Hand Dryer
- Air Volume/Velocity: 36km/h
- Drying time: 20-30 (secs)
- Cut-out Temperature: 105°C

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Product Summary

### Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	240 x 240 x 200 mm
Ingress Protection (IP)	IPX1
Electrical	
Output Rating (W)	2000W
Input Voltage (V)	220-240V AC
Frequency (Hz)	50/60Hz
Heating Power Output	1900W
Current (Amps)	10A
Approvals	CE RoHS
Rotation Speed - (rpm)	2600
Performance Data	
Suitable Mounting Position	Wall Mounted only
Air Volume/Velocity (cb/h)	36km/h
Air Speed (M/sec)	12 m/s
Working Air Temperature (°C)	45-60 °C
Nominal Air Flow (M³/h - L/min)	152
Effective Air Flow (M³/h - L/min)	145
Noise level (dB)	40dB
Drying time (secs)	20-30 (secs)
Protection Time (secs)	<60 (secs)
Cut-out Temperature (°C)	105°C
Rotation speed (rpm)	2600
Construction	
Body	ABS
Motor	100W
Weight	2.Kg
Warranty Years	1Yr
Other	
Applications	Suitable for bathrooms and washrooms

