

Model. HDM25ACHR

Heavy Duty Automatic - Chrome 2.5kW Non-Inductive Motor with Over Heat Protection



Features & Benefits

- BS EN60335-2:2003 compliance
- Comes with 3 Core x 1.5mm 1 Mtrs 13A cable
- Durable motor, vandal-proof and energy efficient in high use areas
- 360° rotating nozzle to suit hand or face use with thermo-guard protection

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Satin Chrome
Dimensions (mm)	270x240x200mm
Ingress Protection (IP)	IPX1
Electrical	
Output Rating (W)	2500W
Input Voltage (V)	240V AC
Frequency (Hz)	50/60Hz
Current (Amps)	11.4
Approvals	CE, GS, RoHS
Rotation Speed - (rpm)	Automatic
Performance Data	
Suitable Mounting Position	Wall mounting
Air Volume/Velocity (cb/h)	270 Cb/h
Air Speed (M/sec)	30m/s
Noise level (dB)	85
Drying time (secs)	10-15 secs (drying time)
Cut-out Temperature (°C)	Over Heat Protection
Construction	
Body	Heavy Duty Chrome Steel Construction
Motor	Non-Inductive Motor
Weight	5.5
Warranty Years	1
Other	
Applications	Suitable for use in high traffic areas such as service station, clubs, railway stations and similar projects