

## Model. HDM25AWHI

Heavy Duty Automatic - White 2.5kW with Non-Inductive Motor with Over Heat Protection

### Features & Benefits

- BS EN60335-2:2003 compliance
- Comes with 3 Core x 1.5mm 1 Mtrs 13A cable
- Durable motor, vandal-proof and energy efficient in high use areas
- 360° rotating nozzle to suit hand or face use



### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	White (Powder Coated)
Dimensions (mm)	270x240x200mm
Ingress Protection (IP)	IPX1
Electrical	
Output Rating (W)	2500W
Input Voltage (V)	240V AC
Frequency (Hz)	50/60Hz
Current (Amps)	11.4
Approvals	CE, GS, RoHS
Rotation Speed - (rpm)	Automatic
Performance Data	
Suitable Mounting Position	Wall mounting
Air Volume/Velocity (cb/h)	270 Cb/h
Air Speed (M/sec)	30m/s
Noise level (dB)	85
Drying time (secs)	10-15 secs (drying time)
Protection Time (secs)	Over Heat Protection
Construction	
Body	White plated diecast aluminium
Weight	5.5kg
Warranty Years	1Yr
Other	
Applications	Suitable for use in high traffic areas such as service station, clubs, railway stations and similar projects