

Model. HDM25PCHR

Heavy Duty Push Button - Chrome with 2.5kW Non-Inductive Motor

Features & Benefits

- Heavy duty chrome steel construction and BS EN60335-2:2003 compliance
- Complete with over heat protection and 3 Core x 1.5mm 1 Mtrs 13A cable
- Durable motor, vandal-proof and energy efficient in high use areas
- 360° rotating nozzle to suit hand or face use with thermo-guard protection
- Fitted with push button: 35 second every press / 10-15 secs (drying time)



Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Satin Chrome
Dimensions (mm)	270x240x200mm
Ingress Protection (IP)	IPX1
Electrical	
Output Rating (W)	2500W
Input Voltage (V)	220-240v
Frequency (Hz)	50/60Hz
Heating Power Output	11.4
Approvals	CE, GS, RoHS, BS EN60335-2:2003
Performance Data	
Suitable Mounting Position	Wall mounting
Air Volume/Velocity (cb/h)	270 Cubic Mtr/hr
Air Speed (M/sec)	30m/s
Noise level (dB)	85dB
Drying time (secs)	10-15 secs (drying time)
Cut-out Temperature (°C)	Over Heat Protection
Construction	
Body	Heavy Duty Chrome Steel Construction
Motor	Non-Inductive Motor
Weight	5.5kg
Warranty Years	1yr
Other	
Applications	Suitable for use in high traffic areas such as service station, clubs, railway stations and similar projects