PROFIX





Model. I12IST

Interlocking Junction Box

Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

| Product Colour/Finsh Grey Dimensions 85x85x37 Body Material PP Sealable No Weatherproof No Knockouts x12 Approvals VDE Warranty 1 Ambient Temperature -25 to 40c | General Information | |
|--|--------------------------|----------------------|
| Body Material PP Sealable No Weatherproof No Knockouts x12 Approvals VDE Warranty 1 | Product Colour/Finsh | Grey |
| Sealable No Weatherproof No Knockouts x12 Approvals VDE Warranty 1 | Dimensions | 85x85x37 |
| Weatherproof No Knockouts x12 Approvals VDE Warranty 1 | Body Material | PP |
| Knockouts x12 Approvals VDE Warranty 1 | Sealable | No |
| Approvals VDE Warranty 1 | Weatherproof | No |
| Warranty 1 | Knockouts | x12 |
| · | Approvals | VDE |
| Ambient Temperature -25 to 40c | Warranty | 1 |
| | Ambient Temperature | -25 to 40c |
| Rel Humidity 50% at 40c | Rel Humidity | 50% at 40c |
| Electrical | Electrical | |
| IP Rating IP 55 | IP Rating | IP 55 |
| Class II | Class | |
| Rated Cross Section 2.5 | Rated Cross Section | 2.5 |
| Rated Insulation Voltage 400v | Rated Insulation Voltage | 400v |
| Others | Others | |
| Application Domestic, Commercial | Application | Domestic, Commercial |