

## Model. IDL6CHR

6W Integrated Fire Rated Downlight - Chrome (550Lm)

### Features & Benefits

There are currently no features entered for this product item.

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only



### Technical Specifications

General Information	
Product Colour/Finish	Chrome
Dimensions (mm)	86.5x76
Cut-Hole Ø (mm)	73
Ingress Protection	IP 65
Electrical	
Input Voltage (V)	220-240
Frequency (Hz)	50/60
Wattage (W)	6
Dimmable (Y/N)	Y
Approvals	CE, Building Regs B, C, E, L
Class	I
Inrush Current (mA)	2.16 A
Performance Data	
Useful Lumen Output	550
Lumens (Per Watt)	90
Power Factor	>0.7
Average Lifespan (Hours)	25000
CRI: Ra	80
Colour Temperature (K)	3000
Beam Angle (°)	38
LED Type	Hongli COB
Number of LED (pcs)	1
Energy Rating (ErP)	A++ To A
Sensor	
Emergency	
Construction	
Body Material	Metal
Diffuser Material	Glass Lens
Weight	206g
Warranty Period (Years)	3
Other	
Applications	Domestic, Commercial

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**