



## Model. IFL100

100W LED COB Industrial Floodlight 100-240v

### Features & Benefits

- Perfect for outdoors use with die-cast Aluminium body and Over 70% energy saving
- Anticorrosive paint and tempered glass for durable external usage
- Adjustable and suitable for use in multiple application use with improved heat dissipation

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	444x353x66mm
Ingress Protection	IP65
Electrical	
Input Voltage (V)	AC100-240V
Frequency (Hz)	50/60Hz
Wattage (W)	100W
Wattage Equivalent (W)	250W
Dimmable (Y/N)	N
Approvals	CE
Class	Class I
Performance Data	
Useful Lumen Output	8500Lm
Lumens (Per Watt)	90Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	30000Hrs
CRI: Ra	>72
Colour Temperature (K)	6000K
Beam Angle (°)	70°
LED Type	COB
Number of LED (pcs)	2PCS
Energy Rating (ErP)	A
Sensor	
Emergency	
Construction	
Body Material	Aluminum
Diffuser Material	Glass
Weight	4.8KGS
Warranty Period (Years)	5 Years
Other	
Applications	Domestic and commercial applications

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**