

Model. BHP100

100W Rectangular B22 Polycarbonate

Features & Benefits

- Made to BS60598-2 and available in medium and full size
- Gasket - Silicon rubber fits between body and visor
- Fitted with magnetic ballast (Energy Saving only)
- 20mm knockouts provided at base and both ends

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Black
Dimensions (mm)	240x115x100mm
Ingress Protection	IP65
Electrical	
Input Voltage (V)	240v
Frequency (Hz)	50hz
Wattage (W)	100W
Dimmable (Y/N)	If Using Dimmable Bulb
Approvals	CE/ BS-EN60598-2
Class	II
Performance Data	
Beam Angle (°)	120°
Sensor	
Emergency	
Construction	
Body Material	Polycarbonate
Diffuser Material	Prismatic diffuser which withstands temperatures up to 115°C
Weight	1.28kg
Warranty Period (Years)	1Yr
Other	
Applications	Offices/ Commercial Building/ Hospitals/ Garages/ Indoor & Outdoor

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE