

Model. LEDAC16NT

6' Single Anti-Corrosive Empty Body Fluorescent Fitting With Clear Prismatic Diffuser (To use with LED Tubes) IP65

Features & Benefits

- High energy efficiency, long life and maintenance free
- Sealed tough anti-corrosive luminaries for harsh environments
- Optimised for LED Fluorescent use
- Optional meta clips available for extra security construction
- Surface mounted or suspended by chains
- Suitable for use in high humidity internal or external areas
- Supplied without fluorescent Tube
- Matching Tubes from CED 18W PC Tube (LEDT4) or 15W Glass Tube (LEDT4GS/NW)
- Comes complete with terminal blocks for series wiring
- Supplied with led driver and dedicated led light source with new aluminium heat sync

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	187x11x10cm
Ingress Protection (IP)	IP65
Electrical	
Input Voltage (V)	240V
Frequency - (Hz)	50/60Hz
Dimmable (Y/N)	N
Approvals	BS EN60309
Performance Data	
Fixing Centre (mm)	1380mm
Type (Single or Twin)	Single
Construction	
Body Material	Grey Poly-carbonate body
Diffuser Material	Clear Prismatic Diffuser
Warranty Period (Years)	2yr
Others	
Applications	Suitable for installation in damp and harsh environments in domestic, commercial & industrial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE