

Model. LEDBRICK1WHI

Brick lite diecast aluminium IP54 White LED Exact Brick Size

Features & Benefits

- Fitted with stainless steel perimeter or horizontal strip cover
- Opal diffuser with spring clips
- Diecast aluminium base housing with either clear or opal diffuser
- Fitted with white LED colour outputs
- Also available in a choice of white LED colour output



Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

General Information	
Product Colour/Finish	Silver grey front plate
Dimensions (mm)	233x95x80mm
Cut-Hole Ø (mm)	230x95mm
Ingress Protection	IP65
Electrical	
Input Voltage (V)	240V
Frequency (Hz)	50/60Hz
Wattage (W)	6W
Wattage Equivalent (W)	15W
Dimmable (Y/N)	N
Approvals	CE
Class	I
Performance Data	
Useful Lumen Output	150Lm
Lumens (Per Watt)	31Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	35,000Hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	60°
LED Type	SMD
Number of LED (pcs)	70pcs
Energy Rating (ErP)	A
Sensor	
Emergency	
Construction	
Body Material	Diecast Aluminium Base & Stainless Steel Front/Grill Panel
Diffuser Material	Opal Diffuser
Warranty Period (Years)	1Yr
Other	
Applications	Stairways, corridors, Utility Rooms & High Impact Areas

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE