





Model. MCU10S

Metal Consumer Unit with main switch as isolator

Features & Benefits

- 8 Free Way Main Switch Board
- New modern user friendly design quick and easy to install.
- Full metal steel casement construction for safety and to impede fire entry. .
- Steel drop down solid cover to protect against dust and retard fire entry. Separate earth and neutral terminal at the top for easy wiring and identification.
- .
- Generous internal cabling space above RCBO's (for time saving wiring).
 Easy knockouts all round for trucking entry and wall mounting.
- Compact and robust construction.
- Large terminals.None combustible cover blanks.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- · Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	23.5x23.7x11
Ingress Protection (IP)	IP20
Electrical	
Rated Votage	230 - 240V
Frequency (Hz)	50Hz
Sensitivity	30mA
Terminal Capacity (2mm)	n/a
Performance Data	
Specifications	Board IEC - 61439-3
Isolator	100A DP
Filled with MCB	N
Approvals	RoHS, CE
Construction	
Weight	2.355Kg
Warranty Years	1yr
Body Material	Metal
Knockouts	20-20-25-32
Number of ways	10
Number of free ways	8
Other	
Applications	Domestic, commercial applications

