

Model. MCU18S

Metal Consumer Unit with main switch as isolator

Features & Benefits

- 16 Free way main switch board
- New modern user friendly design quick and easy to install.
- Full metal steel casement construction for safety and to impede fire entry.
- Steel drop down solid cover to protect against dust and retard fire entry.
- Separate earth and neutral terminal at the top for easy wiring and identification.
- Generous internal cabling space above RCBO's (for time saving wiring).
- Easy knockouts all round for trucking entry and wall mounting.
- Compact and robust construction.
- Large terminals.
- None combustible cover blanks.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	379x237x11mm
Ingress Protection (IP)	IP20
Electrical	
Rated Voltage	230 - 240V
Frequency (Hz)	50/60Hz
Sensitivity	30mA
Terminal Capacity (mm)	n/a
Performance Data	
Specifications	Board IEC - 61439-3
Isolator	100A DP
RCD	None
Filled with MCB	N
Approvals	CE
Construction	
Weight	3.269Kg
Warranty Years	1yr
Body Material	Metal Clad
Knockouts	32-25-20-20-20-25-32
Number of ways	18
Number of free ways	16 ways
Other	
Applications	Domestic, commercial applications

