

Model. MCU24SL

20 Free Way 2 Tier Consumer Unit Split Load (Without MCB)



Features & Benefits

- New modern user friendly design quick and easy to install.
- Full metal steel casement construction for safety and to impede fire entry.
- Steel drop down solid cover to protect against dust and retard fire entry.
- Separate earth and neutral terminal at the top for easy wiring and identification.
- Generous internal cabling space above RCBO's (for time saving wiring).
- Easy knockouts all round for trucking entry and wall mounting.
- Compact and robust construction.
- Large terminals.
- None combustible cover blanks.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	465 x 280 x 110mm
Ingress Protection (IP)	IP20
Electrical	
Rated Voltage	230 - 240V
Frequency (Hz)	50Hz
Sensitivity	30mA
Terminal Capacity (mm ²)	n/a
Performance Data	
Specifications	Board IEC - 61439-4
Isolator	125A DP
RCD	1x 80A 2P
Filled with MCB	N
Approvals	RoHS, CE
Construction	
Weight	5.44Kg
Warranty Years	1yr
Body Material	Metal
Knockouts	32-20-20-25-32
Number of ways	24
Number of free ways	19
Other	
Applications	Domestic, commercial applications