

No Image

Model. MCU6RTA

Metal Consumer Unit with RCD as main switch

Features & Benefits

- 6 ways main switch board
- New modern user friendly design quick and easy to install.
- Full metal steel casement construction for safety and to impede fire entry.
- Steel drop down solid cover to protect against dust and retard fire entry.
- Separate earth and neutral terminal at the top for easy wiring and identification.
- Generous internal cabling space above RCBO's (for time saving wiring).
- Easy knockouts all round for trunking entry and wall mounting.
- Compact and robust construction.
- Large terminals.
- Non combustible cover blanks.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	16.3x23.7x11
Ingress Protection (IP)	IP20
Electrical	
Rated Voltage	230 - 240V
Frequency (Hz)	50Hz
Sensitivity	30mA
Terminal Capacity (mm)	n/a
Performance Data	
Specifications	Board IEC - 61439-3
Isolator	RCD
RCD	63A DP
Filled with MCB	N
Approvals	Board IEC - 61439-3
Construction	
Weight	1.825Kg
Warranty Years	1yr
Body Material	Metal
Knockouts	20-20
Number of ways	6
Number of free ways	4
Other	
Applications	Domestic, commercial applications