





Twin LED Batten Fitting 4Ft 50W Emergency

## Features & Benefits

There are currently no features entered for this product item.

#### Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

# **Product Summary**

## **Technical Specifications**

'	
General Information	
Product Colour/Finish	White
Dimensions (mm)	1218 x 65 x 57
Ingress Protection (IP)	IP 20
Electrical	
Input Voltage (v)	220-240
Frequency (Hz)	50/60
Wattage (W)	50
Dimmable (Y/N)	N
Approvals/Certifications	CE
Class	
Inrush Current (mA)	<10A
Performance Data	
Useful Lumen Output	4900
Lumens (Per Watt)	117
Power Factor	0.9
Average Lifespan (Hours)	25000
CRI: Ra	80
Colour Temperature (K)	4000
Beam Angle (°)	120
LED Type	Sinotron 2835
Number of LED (pcs)	294
Energy Rating (ErP)	E
Sensor	
Emergency	
Emergency Period (Hours)	3
Construction	
Body Material	Steel
Diffuser Material	PC Opal
Warranty Period (Years)	3
Other	
Applications	Domestic, Commercial

# LIGHTING DESIGN

#### **IMPORTANT!**

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE

