

## Model. OVFL10PIR

10W LED Slim curved floodlight with PIR and integrated junction box, 800Lm, 6500K



### Features & Benefits

- Durable, slim and curved design with in-built integrated junction box and fitted with a PIR with manual override function
- Complete with 3x1.0mm2 cable and energy-saving LED luminaire
- Black powder coated die-cast aluminium body with heat dissipater and clear tempered glass
- Angled bracket for easy installation and flexible positioning

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	Black
Dimensions (mm)	190x142x48mm
Ingress Protection	IP54 (Floodlight without PIR IP65)
Electrical	
Input Voltage (V)	220-240V
Frequency (Hz)	50/60Hz
Wattage (W)	10W
Dimmable (Y/N)	None dimmable
Approvals	CE-LVD, CE-EMC and RoSH
Class	I
Inrush Current (mA)	80mA
Performance Data	
Useful Lumen Output	800lm
Lumens (Per Watt)	80lm
Power Factor	>0.50
CRI: Ra	>70
Colour Temperature (K)	6500K
Beam Angle (°)	110°
LED Type	SMD2835
Number of LED (pcs)	14pcs
Sensor	
Sensor Interval (mins)	7sec~10mins
Sensor Range (Mtrs / °)	Max. 10m
Emergency Construction	
Body Material	Diecast Aluminium body
Diffuser Material	Clear tempered glass
Weight	375g
Warranty Period (Years)	2yrs
Other	
Applications	Architecture, parks and gardens, facades, roof top and billboard

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**