

Model. OVFL30

30W LED Slim curved floodlight with IP65 integrated junction box, 2400Lm, 6500K

Features & Benefits

- Durable, slim and sleek design with integrated junction box
- Angled bracket for easy installation and flexible positioning
- Complete with 3x1.0mm2 cable and energy-saving LED luminaire
- Black powder coated die-cast aluminium body with heat dissipater and clear tempered glass



Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|-------------------------|--|
| Product Colour/Finish | Black |
| Dimensions (mm) | 175x125x55mm |
| Cut-Hole Ø (mm) | N/A |
| Ingress Protection | IP65 |
| Electrical | |
| Input Voltage (V) | 220-240V |
| Frequency (Hz) | 50/60Hz |
| Wattage (W) | 30W |
| Dimmable (Y/N) | None dimmable |
| Approvals | CE-LVD, CE-EMC and RoSH |
| Class | I |
| Inrush Current (mA) | 135mA |
| Performance Data | |
| Useful Lumen Output | 2400lm |
| Power Factor | >0.90 |
| CRI: Ra | >70 |
| Colour Temperature (K) | 6500K |
| Beam Angle (°) | 110° |
| LED Type | SMD2835 0.5W |
| Number of LED (pcs) | 42pcs |
| Sensor | |
| Sensor Interval (mins) | 7sec~10mins |
| Sensor Range (Mtrs / °) | Max. 10m |
| Emergency | |
| Construction | |
| Body Material | Diecast Aluminium body |
| Diffuser Material | Clear tempered glass |
| Weight | 430g |
| Warranty Period (Years) | 2yrs |
| Warranty Period (Years) | 2yrs |
| Other | |
| Applications | Architecture, parks and gardens, facades, roof top and billboard |

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE