

Model. PBC12CW

LED GLS Lamp 12W - BC (B22) Lamp Base - Opal Diffuser - 6500K



Features & Benefits

- Instant light without flickering, mercury free and no UV output
- Polycarbonate resistant cover and BC (B22) Lamp Base
- Up to 80% energy saving, longer life and more eco-friendly
- Fitted with a lightweight thermal plastic shell that dissipates heat more effectively
- Non-Dimmable and also available in 3000K, Dimmable, 7W, 10W, 15W, 18W and ES (E27) Lamp Base

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	Ø60 x 120mm
Ingress Protection (IP)	IP20
Electrical	
Input Voltage (v)	220-240V
Frequency (Hz)	50/60Hz
Wattage (W)	12W
Wattage Equivalent (W)	75W
Dimmable (Y/N)	N
Approvals/Certifications	CE / ERP
Class	I
Performance Data	
Useful Lumen Output	1100Lm
Lumens (Per Watt)	91Lm/w
Power Factor	>0.5
Average Lifespan (Hours)	30,000Hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	300°
LED Type	SMD2835
Number of LED (pcs)	14(pcs)
Energy Rating (ErP)	A+
No. Switches (max.)	>15000
Sensor	
Emergency Construction	
Body Material	Thermoplastic/Aluminium
Diffuser Material	Opal diffuser
Weight (g)	0.080g
Warranty Period (Years)	3Yrs
Working temperature (°C)	-25C° - +40C°
Other	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE