

Model. PCKIT

Photocell kit - Electronic Includes Head and Wall Bracket



Features & Benefits

- Photo diode Sensor with a typical load of 2x250W HPS or 1000W Tungsten
- Kit includes head & wall bracket and Nema socket 20mm
- Made to BSEN 5008-1 with upto 5000 electrical life cycles
- 5A maximum switching capacity and 10-15 Seconds switching delay.
- Enclosures made from UV stabilised polycarbonate, fit for requirement of UL94 5VA flammability standards

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

General Information	
Product Colour/Finish	Opal Head / Black Body
Dimensions (mm)	80x129x85mm
Ingress Protection	IP54
Electrical	
Input Voltage (V)	240V AC
Frequency (Hz)	50/60Hz
Approvals	CE
Class	II
Performance Data	
Sensor	
Emergency	
Construction	
Body Material	Opal Head / Black Body
Diffuser Material	Prismatic plastic
Weight	Nett: 0.171Kg / Gross: 0.230Kg
Warranty Period (Years)	1Yr
Other	
Applications	Suitable for road lamps, courtyard lamps, hallway lamps & door lamps

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE