

Model. PIR360SUR

360° Surface Mounting PIR Motion Sensor IP20

Features & Benefits

- TUV-BS approved
- For use with new and existing lighting
- Surface mounting
- Time adjustment of 5 seconds to 7 minutes
- Manual override allows the floodlight to run continuously
- Lumen control allows the unit to be activated at any desired level of darkness

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour / Finish	White
Dimensions - (mm)	Ø110x39mm
Ingress Protection (IP)	IP20
Electrical	
Wattage - (W)	0.5W
Frequency - (Hz)	50/60Hz
Power source	220-240v
Detection Distance	6m (radius)
Ambient Light	Day or night operation
Time Delay	5secs - 5mins
Detection Range	360°
Detection Motion Speed	0.6-1.5m/s
Installation Height	2.8 - 3m
Performance Data	
Approvals / Accreditations	CE, RoHS
Construction	
Body Material	Polycarbonate
Weight	0.6kg
Warranty Years	1Yr
Others	
Applications	Domestic, commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE