

## Model. PLL4CCT2

LED Plastic Link Light with CCT2 - 4Watts - 380lm - 310mm

### Features & Benefits

- 1 x 1.6 Metres live end cable (no plug)
- 1 x 270mm flexible direct interconnecting line
- Fixing screws, straight and angled fixing brackets
- Connect upto 6pcs Max

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

<b>General Information</b>	
Product Colour/Finish	White
Dimensions (mm)	310x36mm
Ingress Protection	IP20
<b>Electrical</b>	
Input Voltage (V)	220-240V
Frequency (Hz)	50/60Hz
Wattage (W)	4W
Dimmable (Y/N)	N
Approvals	CE
Class	II
<b>Performance Data</b>	
Useful Lumen Output	380lm
Lumens (Per Watt)	90lm/w
Power Factor	>0.4
Average Lifespan (Hours)	30000hrs
CRI: Ra	>80
Colour Temperature (K)	2700/4000k
Beam Angle (°)	150°
LED Type	SMD 2835
Energy Rating (ErP)	F
No. Switches (max.)	15,000
<b>Sensor</b>	
<b>Emergency</b>	
<b>Construction</b>	
Body Material	White Plastic
Diffuser Material	White Plastic
Warranty Period (Years)	3yrs
Working Temperature	-25C° - + 40C°
<b>Other</b>	
Applications	Under cupboard, domestic, commercial

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**