

Model. PLL4WW

LED Plastic Link Light - 4Watts - 380lm - 310mm

Features & Benefits

- Links upto 6pcs Max
- 1 x 270mm flexible direct interconnecting line
- 1 x 1.6 Metres live end cable (no plug)
- Fixing screws, straight and angled fixing brackets



Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	310x36mm
Ingress Protection	IP20
Electrical	
Input Voltage (V)	220-240Vac
Frequency (Hz)	50/60Hz
Wattage (W)	4W
Dimmable (Y/N)	N
Approvals	CE, UKCA
Class	II
Performance Data	
Useful Lumen Output	380lm
Lumens (Per Watt)	90lm/w
Power Factor	>0.5
Average Lifespan (Hours)	30000hrs
CRI: Ra	>80
Colour Temperature (K)	3000k
Beam Angle (°)	150°
LED Type	SMD 2835
Energy Rating (ErP)	F
No. Switches (max.)	30,000
Sensor	
Emergency	
Construction	
Body Material	White Plastic
Diffuser Material	PC opal diffuser
Warranty Period (Years)	3yrs
Working Temperature	-25C° - + 40C°
Other	
Applications	Under cupboard, domestic, commercial

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE