





IP65 LED Polar Bulkheads with Emergency backup - 1200Lm - 15W - 4000K,



- Slimline design, economical & functional
- Complete with 3 Hour Emergency Fitting
- Fitted with top quality SMD2835 Sinotron LEDs
- Hinged gear tray for quick easy installation



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
 Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

real openineations	
General Information	
Product Colour/Finish	White
Dimensions (mm)	336.5 x 105.6
Ingress Protection	IP 65
Electrical	
Input Voltage (V)	220-240
Frequency (Hz)	50/60
Wattage (W)	15
Dimmable (Y/N)	N
Approvals	CE
Class	II
Inrush Current (mA)	5A
Performance Data	
Useful Lumen Output	1200
Lumens (Per Watt)	80
Power Factor	>0.5
Average Lifespan (Hours)	30000
CRI: Ra	80
Colour Temperature (K)	4000
Beam Angle (°)	120
LED Type	SMD2835 Sinotron
Number of LED (pcs)	96
Energy Rating (ErP)	A
Sensor	
Emergency	
Emergency Output (W)	2
Emergency Period (Hours)	3
Construction	
Body Material	PC
Diffuser Material	PC
Warranty Period (Years)	3
Other	
Applications	Suitable for indoor/outdoor domestic/commercial use

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE

