





100Amp 3P + 1Aux 415v Moulded

Features & Benefits

- 3P + 1Aux IP65 (weather proof) 440V 50Hz ABS polycarbonate enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts 2 x 25mm on each side
- Colour Handle Red/Yellow for main emergency switch, Enclosure Dark Grey, Body Light Grey
 Standards & Approvals BS EN60947, IEC947-1-3, CSA, RU, UL, CE

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
Dimensions	190 x 280 x 130mm
Mounting	B31L-RD
Ingress Protection	IP65
Electrical	
Load (Amp)	415v
Voltage (Amps)	100A
Number of Knockouts	2 x 25mm
Number of Poles	3P + 1Aux
Standards	BS EN60947, IEC947-1-3
Approvals	CE, UL, Intertek
Construction	
Body Material	Polycarbonate
Weight	2.1Kg
Warranty (Years)	1Yr
Other	
Application	Suitable for 'Commercial & Industrial Applications'
	• •

