

Model. RS1004SE

100Amp 3P + 1Aux Rotary Isolator 415v



Features & Benefits

- 3P + 1Aux, IP65 (weather proof) 440V - 50Hz steel enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts - 2 x 25mm on each side
- Colour - Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
- Standards & Approvals - BS EN60947, IEC947-1-3, CSA, RU, UL, CE

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
Dimensions	190 x 280 x 130mm
Fixing Centre	160 x 172mm
Mounting	SB31L-RD
Ingress Protection	IP54
Electrical	
Load (Amp)	415v
Voltage (Amps)	100A
Number of Knockouts	2 x 25mm
Number of Poles	3P + 1Aux
Standards	BS EN60947, IEC947-1-3
Approvals	CE UL, Intertek
Construction	
Body Material	Sheet steel
Weight	3.1Kg
Warranty (Years)	1Yr
Other	
Application	Suitable for 'Commercial & Industrial Applications'