

## Model. RS254

25Amp 3P + 1Aux, 11kW 415v Rotary Isolator

### Features & Benefits

- 3P + 1Aux, IP65 (weather proof) 440v - 50Hz ABS polycarbonate enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts - 2 x 20mm on each side
- Colour - Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
- Standards & Approvals - BS EN60947 IEC947-1-3, CSA, RU, UL, CE

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
Dimensions	125 x 100 x 73mm
Fixing Centre	80 x 115mm
Mounting	B31SM-RD
Ingress Protection	IP65
Electrical	
Load (Amp)	415v
Voltage (Amps)	25A
Number of Knockouts	2 x 20mm
Number of Poles	3P + 1Aux
Standards	BS EN60947, IEC947-1-3
Approvals	CE, UL, Intertek
Construction	
Body Material	Polycarbonate
Weight	0.5Kg
Warranty (Years)	1Yr
Other	
Application	Suitable for 'Commercial & Industrial Applications'

