

## Model. RS324HD

32A 3P + 1Aux, Heavy Duty Diecast Rotary Isolator

### Features & Benefits

- 3P + 1Aux, IP65 (weather proof) 415v - 50Hz, Switch mounted in Aluminium enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts - 2 x 25mm on each side
- Colour - Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
- Standards & Approvals - BS EN60947, IEC947-1-3, CSA, RU, UL, CE

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

| General Information   |   |
|-----------------------|---|
| Product Colour/Finish | Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey |
| Dimensions            | 150 x 140 x 100mm   |
| Fixing Centre         | 80 x 25mm   |
| Mounting              | AB31M - RD  |
| Ingress Protection    | IP65  |
| Electrical            |   |
| Load (Amp)            | 415v  |
| Voltage (Amps)        | 32A   |
| Number of Knockouts   | 2 x 20mm  |
| Number of Poles       | 3P + 1Aux   |
| Approvals             | CE UL, Intertek   |
| Construction          |   |
| Body Material         | Aluminium   |
| Weight                | 1.3Kg   |
| Warranty (Years)      | 1   |
| Other                 |   |
| Application           | Suitable for 'Commercial & Industrial Applications'                                   |

