

## Model. RS404

40Amp 3P + 1Aux, 18.5kW 415v



### Features & Benefits

- 3P + 1Aux, IP65 (weather proof) 440v - 50Hz ABS Polycarbonate enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts - 2 x 25mm on each side
- Colour - Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
- Standards & Approvals - BS EN60947, IEC947-1-3, CSA, RU, UL, CE

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Product Colour/Finish	Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
Dimensions	175 x 125 x 90mm
Fixing Centre	105 x 155mm
Mounting	B31M-RD
Ingress Protection	IP65
Electrical	
Load (Amp)	415v
Voltage (Amps)	40A
Number of Knockouts	2 x 25mm
Number of Poles	3P + 1Aux
Standards	BS EN60947, IEC947-1-3
Approvals	CE UL, Intertek
Construction	
Body Material	Polycarbonate
Weight	0.75Kg
Warranty (Years)	1
Other	
Application	Suitable for 'Commercial & Industrial Applications'