

Model. RS634HD

63A 3P + 1Aux, Heavy Duty Diecast Rotary Isolator

Features & Benefits

- 3P + 1Aux, IP65 (weather proof) 415v - 50Hz, Switch mounted in Aluminium enclosure
- Padlock facility to lock in "off position" preventing the switch being used by unauthorised persons
- Knockouts - 2 x 25mm on each side
- Colour - Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
- Standards & Approvals - BS EN60947, IEC947-1-3, CSA, RU, UL, CE

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Handle Red/Yellow for main emergency switch, Enclosure - Dark Grey, Body - Light Grey
Dimensions	150 x 140 x 100mm
Fixing Centre	130 x 120mm
Mounting	AB31M - RD
Ingress Protection	IP65
Electrical	
Load (Amp)	415v
Voltage (Amps)	63A
Number of Knockouts	2 x 20mm
Number of Poles	3P + 1Aux
Approvals	CE UL, Intertek
Construction	
Body Material	Aluminium
Weight	1.3Kg
Warranty (Years)	1
Other	
Application	Suitable for 'Commercial & Industrial Applications'

